

THE ADHESIVE · SOUNDPROOFING SYSTEM

The mat's adhesive, in plain words.

When the Mapesonic soundproofing mat goes in, a second adhesive joins the job: MAPEI Ultrabond S955 1K, which bonds the mat to the subfloor before the floor is glued over it. This page is the plain English summary, drawn from the manufacturer's technical data sheet, available in full whenever you ask.

**One component, no mixing.**

S955 1K is a one component, silylated polymer adhesive: ready to use straight from the pail, no catalyst, no mixing, with excellent ridge holding as the mat is seated into it. It is happy over cementitious screeds, old ceramic, terrazzo and heated substrates alike.

MAPEI ULTRABOND S955 1K TECHNICAL DATA SHEET · ONE COMPONENT SILYLATED POLYMER

**Clean by design.**

Totally solvent free, with a very low emission level of volatile organic compounds, certified EC1 Plus, and no hazard or risk symbols on the pail. The layer nobody ever sees still meets the standard of everything we lay.

EMICODE EC1 PLUS · SOLVENT FREE · NO HAZARD STATEMENTS

**Its place in the stack.**

S955 1K holds exactly one position: between the prepared slab and the Mapesonic mat. The timber above the mat is bonded with ECO 995 as on every other job, so each adhesive does the job it is best at.

SLAB · S955 1K · MAPESONIC MAT · ECO 995 · TIMBER

**Already in the soundproofing price.**

You will not find S955 as a line of its own: the \$55/m² soundproofing price on your quote includes both the mat and this adhesive. One number, the whole quiet system.

INCLUDED IN THE \$55/M² SOUNDPROOFING PRICE